

optibelt *RBK*

New engine design is putting an increasing emphasis on space saving. Small pulley diameters necessitating thin, flexible belts are often the result. Optibelt ribbed belts are ideal products for today's serpentine drives and operate all of the accessories quietly and smoothly.

Advantages

- High transmission ratios
- High power transmission
- Minimum slip
- Largely oil- and temperature-resistant
- Vibration-free and quiet
- Low stretch


In passenger cars, commercial vehicles and buses, Optibelt ribbed belts drive the ancillaries such as the generator, the air conditioning compressor, the power steering pump and the turbocharger smoothly and quietly.

Examples of Applications

- | | |
|--|---|
| Combination of trapezoidal ribs on a rubber core | ■ high power transmission, high wear resistance, quiet running |
| Single belt characteristic | ■ vibration-free as well as insensitive to pulsating running and intermittent loads |
| Polyester tension cord | ■ excellent tension behaviour, with low stretch |
| Low section height | ■ very flexible, extremely small pulley diameters, serpentine drives (using reverse bend idlers), good heat resistance, long life |



RBK



- 1 Fibre reinforced top surface: wear-resistant chloroprene rubber compound
- 2 Tension cord: low stretch polyester
- 3 Cushion rubber: high adhesion chloroprene cushion compound
- 4 Base: chloroprene rubber compound

Sections:

PJ; PK; DPK

Sizes:

2 PK	from	786 to	905 mm
3 PK	from	550 to	1285 mm
4 PK	from	560 to	1520 mm
5 PK	from	625 to	2055 mm
6 PK	from	675 to	2680 mm
7 PK	from	870 to	2355 mm
8 PK	from	800 to	2605 mm
9 PK	from	1200 to	4145 mm
10 PK	from	1108 to	2063 mm
11 PK	from	1515 to	2055 mm
12 PK	from	1165 to	2500 mm
6 DPK	from	1188 to	1853 mm
7 DPK	from	1360 to	1400 mm

further sizes on request